

Lenovo ThinkVision L2250p - LCD display - TFT - 22"

\$249.99

Plus Shipping and Handling
and any applicable taxes



| | |
|-------------------------------|--|
| Product Description | Lenovo ThinkVision L2250p - LCD display - TFT - 22" |
| Device Type | LCD display / TFT active matrix |
| Color | Business black |
| Dimensions (WxDxH) | 19.9 in x 6.1 in x 15.7 in |
| Weight | 11.5 lbs |
| Diagonal Size | 22" - widescreen |
| Viewable Size | 22" |
| Dot Pitch / Pixel Pitch | 0.282 mm |
| Max Resolution | 1680 x 1050 / 75 Hz |
| Display Positions Adjustments | Height, tilt |
| Color Support | 24-bit (16.7 million colors) |
| Image Aspect Ratio | 16:10 |
| Response Time | 5 ms |
| Image Brightness | 250 cd/m2 |
| Image Contrast Ratio | 1000:1 |
| Digital Video Standard | Digital Visual Interface (DVI) |
| Signal Input | DVI-D, VGA |
| Compliant Standards | FCC Class B certified, CE, MPR II, CSA, UL, TUV, C-Tick, BSMI, VCCI Class B ITE, GOST, cUL, DDC-2B, GS, NEMKO, NOM, SABS, SASO, TUV S, VESA DPMS, VESA FPMPI, IEC 60950, CCC, IC, PSB, JEIDA, DDC/CI, RoHS, TCO Displays 5.0, ISO 9241-307, WEEE |
| Power | AC 120/230 V (50/60 Hz) |
| Power Consumption Operational | 21 Watt |
| Environmental Standards | ENERGY STAR Qualified , EPEAT Gold |
| Manufacturer Warranty | 3 years warranty |

General

| | |
|-----------------|---------------------------------|
| Display Type | LCD display / TFT active matrix |
| TFT Technology | TN |
| Width | 19.9 in |
| Depth | 6.1 in |
| Height | 15.7 in |
| Weight | 11.5 lbs |
| Enclosure Color | Business black |

Display

| | |
|-------------------------------|--|
| Diagonal Size | 22" - widescreen |
| Viewable Size | 22" |
| Dot Pitch / Pixel Pitch | 0.282 mm |
| Max Resolution | 1680 x 1050 / 75 Hz |
| Color Support | 24-bit (16.7 million colors) |
| Max Sync Rate (V x H) | 75 Hz x 83 kHz |
| Video Bandwidth | 205 MHz |
| Response Time | 5 ms |
| Controls / Adjustments | Brightness, contrast, H/V position, input select |
| Display Positions Adjustments | Height, tilt |
| OSD Languages | Chinese (simplified), English, German, French, Italian, Russian, Spanish, Japanese |
| Display Screen Coating | Anti-glare, anti-reflective |
| Tilt Angle | 23 |
| Height Adjustment | 3.1 in |
| Signal Input | DVI-D, VGA |
| Features | HDCP, 72% color gamut |

Image

| | |
|------------------------|-----------|
| Image Aspect Ratio | 16:10 |
| Image Brightness | 250 cd/m2 |
| Image Contrast Ratio | 1000:1 |
| Image Max H-View Angle | 176 |
| Image Max V-View Angle | 170 |

Video Input

| | |
|------------------------|--------------------------------|
| Analog Video Signal | RGB |
| Digital Video Standard | Digital Visual Interface (DVI) |

Expansion / Connectivity

| | |
|------------|---|
| Interfaces | 1 x DVI-D - 24 pin digital DVI 1 x VGA - 15 pin HD D-Sub (HD-15) |
|------------|---|

Miscellaneous

| | |
|----------------------------|--|
| Cables Included | 1 x DVI cable - 6 ft 1 x VGA cable - 6 ft |
| Mounting Kit | Optional |
| Flat Panel Mount Interface | 100 x 100 mm |
| Features | Security lock slot (cable lock sold separately) |
| Compliant Standards | FCC Class B certified, CE, MPR II, CSA, UL, TUV, C-Tick, BSMI, VCCI Class B ITE, GOST, cUL, DDC-2B, GS, NEMKO, NOM, SABS, SASO, TUV S, VESA DPMS, VESA FPM PMI, IEC 60950, CCC, IC, PSB, JEIDA, DDC/CI, RoHS, TCO Displays 5.0, ISO 9241-307, WEEE |

Form Factor Internal

Voltage Required AC 120/230 V (50/60 Hz)

Power Consumption Operational 21 Watt

Power Consumption Stand by / Sleep 1 Watt

Software / System Requirements

OS Required Microsoft DOS, Microsoft Windows XP, Microsoft Windows 7, Microsoft Windows Vista

Environmental Standards

EPEAT Compliant EPEAT Gold

ENERGY STAR Qualified Yes

Manufacturer Warranty

Service & Support 3 years warranty

Service & Support Details Limited warranty - replacement - 3 years - carry-in

Environmental Parameters

Min Operating Temperature 32 °F

Max Operating Temperature 104 °F

Humidity Range Operating 10 - 80%